

# Technical data sheet



## Bindung 2525

## 25%

Bindung 2525 is a vinyl acetate homopolymer dispersion of low viscosity with excellent adhesion power.

### Application field

it is highly recommended for use in paints , especially putty, due to the strength of the adhesive that characterizes the product , despite the percentage of the solid substance in it , compared to other products .

It is particularly suitable for the preparation of adhesives for wood and paper.

It can be used in textile industry as stiffening and sizing agent.

it can be used in carton industry .

### Characteristics

Excellent water resistance

Excellent bond strength

low viscosity dispersion

### Technical data

Test	unit	value	deviation	method
Solid content	%	25	1.0	DIN 53 189/iso 1625
Viscosity	mPa.s	25000	5000	iso 2555; 23 C Brookfield RVT , sp 6 , rem 20 min-1.
pH		4.5	0.5	DIN 53 785 /iso 1148
Density	g/cm <sup>3</sup>	108	0.02	iso 8962

### Film appearance

Test	unit	value
Minimum film forming temp (MFFT)	C	approx 10
Particle size	um	0.1 - 0.2
Film appearance	clear	

### Properties

Technology	polyvinylacetate homopolymer
Base	dispersion polymer ;APEO & low formaldehyde content
Condition	water – based dispersion
Components	one –component
Appearance	milky white

#### Administration

First District, Misr El Taameer Buildings  
Building No. 53 Sheraton Airport Nozha Heliopolis

#### factory

4th Industrial Zone, Inshas, Plot 68



+2 012 00 136 000  
+2 011 47 281 999



info@meemultion.com  
www.meemultion.com



Scan Code